


SPECIFICATIONS:

- 1.DISPLAY MODE: FSTN,TRANSFLECTIVE/POSITIVE.
- 2.OPERATING VOLTAGE: 8.8V
- 3.DRIVING MODE: 1/33DUTY,1/6BIAS
- 4.VIEWING DIRECTION: 6 °CLOCK
- 5.OPERATING TEMPERATURE: -10°C-+60°C
- 6.STORAGE TEMPERATURE: -20°C-+70°C
- 7. DRIVING IC: UC1701/ST7567
- 8.CONNECTOR: CDG

| PIN | NUMBER |
|-----|---------|
| 1 | CS |
| 2 | RES |
| 3 | A0 |
| 4 | D6(SCK) |
| 5 | D7(SDA) |
| 6 | VDD |
| 7 | VSS |
| 8 | VDUT |
| 9 | C3+ |
| 10 | C1- |
| 11 | C1+ |
| 12 | C2+ |
| 13 | C2- |
| 14 | V4 |
| 15 | V3 |
| 16 | V2 |
| 17 | V1 |
| 18 | V0 |



| REV | ECN No. | NATURE OF MODIFICATION | CHANGED BY | DATE |
|-----|---------|------------------------|------------|------------|
| 00 | --- | RELEASED FOR APPROVAL | | 2010-09-18 |

| | | | |
|--------------------------|-------------------------|--|--|
| SHEET: 1 OF 2 | | HDTWELLG 深圳市好威格电子有限公司 TEL:0755-29647561 FAX:0755-29642316 | |
| GENERAL TOL: ±0.20 MM | UNITS MM | | |
| CUS NO: | MODULE NUMBER: 13232 | | |
| PROJECTION | DATE: 4-8-2012 | | |
| APP BY: 70 | CHK BY: LQIN | DO NOT SCALE THIS DRAWING. | |